

Artikelnummer Kendrion / INKOM

Permanent Elektromagnet

Technical Data

Designation	Diameter (d1) x height (h) [mm]	Max. holding force [N]	Nominal power [W]	Thickness counter plate [mm]	Thread (m) x depth (t) [mm]	Clearance (x) [mm]	Cable- / Lead length (L) [mm]	Weight [kg]
01 32002B00	20 x 22	40	3.6	2.5	M4x4.5	10	200	0.04
01 32003B00	35 x 28	160	4.6	3	M4x5	15	200	0.15
01 32005B00	55 x 36	420	8.9	4.5	M5x5	23	200	0.50
01 32007B00	70 x 45	720	13.3	6	M8x5	30	200	0.90
01 32009B00	90 x 48	1200	21.7	7.5	M8x7.5	39	200	1.50
01 32010B00	105 x 56	1600	28	9	M10x10	47	300	2.70
01 32015B00	150 x 63	3500	40.5	12.5	M16x16	68	300	6.40
01 32003A1	1 32.2 x 40	260	6,2	4	M4x4,7	13	200	0,2
PEM1213A	12 x 13	8	1.0	2.0	M4x10	6.5	130	0.01
PEM1515A	15 x 15	30	1.5	2.0	M4x10	7.5	130	0.02
PEM2020A	20 x 20	60	2.0	2.5	M5x12	10	130	0.04
PEM2525A (15% ED)	25 x 25	140	9.6	3.5	M6x15	14	130	0.08